



-  cerisier
-  bois rose










-  cerisier
-  alpi









— [cm]  
—  
—  
— 100  
—  
—  
— 50  
—  
—  
— 0

## HELICON

modèle	Helicon 300	Helicon 400	Helicon 800	Helicon C200
voies / systèmes	3 / 3	3½ / 4	4 / 4	3 / 4
voies / systèmes	3 / 3	3½ / 4	4 / 4	3 / 4
graves / bass-reflex	16.5 cm / en ar.	2x16 cm/en ar.	2x20 cm/en ar.	2x16 cm / en ar.
fréq. de coupure [Hz]	3.4k / 13k	700/3.0k/13k	580/3.0k/13k	2.8k / 13k
rendement	86 dB	88 dB	89.5 dB	90 dB
imp. / charge limite	4 Ω / 200W	4 Ω / 300W	4 Ω / 400W	4 Ω / 250W
linéarité [Hz]	37 - 27k	32 - 27k	31 - 27k	49 - 27k
connexion	bi-wiring	bi-wiring	bi-wiring	bi-wiring
dimensions hxlxp	44 x 21 x 36 cm	103 x 22 x 46 cm	113 x 26 x 49 cm	21 x 65 x 50 cm
exécutions	 / 	 / 	 / 	 / 
PVR /pce.	<b>1990.-</b>	<b>3590.-</b>	<b>4990.-</b>	<b>2690.-</b>

## EUPHONIA

modèle	Euphonia MS4	Euphonia MS5	Euphonia RS3
voies / systèmes	3 / 4	3 / 4	3 / 3
voies / systèmes	3 / 4	3 / 4	3 / 3
graves / bass-reflex	2x16 cm / en ar.	2x20 cm / en ar.	16 cm / -
fréq. de coupure [Hz]	3.0k / 15k	690 / 3.3k / 15k	2.6k / 15k
rendement	88 dB	89 dB	87 dB
imp. / charge limite	4 Ω / 350W	4 Ω / 500W	4 Ω / 250W
linéarité [Hz]	33 - 28k	31 - 28k	64 - 28k
connexion	bi-wiring	tri-wiring	bi-wiring
dimensions hxlxp	102 x 22 x 43 cm	125 x 28 x 56 cm	47 x 20 x 21 cm
exécutions	 / 	 / 	 / 
PVR /pce.	<b>6200.-</b>	<b>8800.-</b>	<b>3200.-</b>



—  
—  
— 40  
—  
—  
— 0